

MDL-III-705 /1~25mW

RED DIODE LASER AT 705nm

Red diode laser at 705nm is made features of round spot, long lifetime, low cost and easy operating, which is widely used in measurement, spectrum analysis, etc.



SPECIFICATIONS

Wavelength (nm)	705 ± 10	
Output power (mW)	>1, 5, 10, ..., 25	
Transverse mode	Near TEM ₀₀	
Operating mode	CW	
Power stability (rms, over 4 hours)	<1%, <3%, <5%	
Warm-up time (minutes)	<5	
Beam divergence, full angle (mrad)	<1.0	
Dimensions of beam at the aperture (mm)	~3, 0	
Beam height from base plate (mm)	24.8	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-III-FDA	PSU-III-LED
Modulation option	TTL/Analog 1Hz-5KHz, 1Hz-10KHz, 1Hz-30KHz, and TTL on/off	
Warranty	1 year	



MxL-III-705	PSU-III-LED	PSU-III-FDA
 <p>139(L)×73(W)×46.2(H) mm³, 0.6kg</p>	 <p>153 (L) ×155(W) ×92 (H) mm³, 1.5kg</p>	 <p>133 (L) ×130(W) ×65 (H) mm³, 1.2kg</p>
		