

MPL-N-532/40~100uJ/150~1000mW

LD PUMPED ALL-SOLID-STATE Q-SWITCHED LASER

All solid state Q-switched laser at 532nm has the features of high peak power, high repetition rate, and short pulse duration, which is widely used in industry, such as marking on highly reflective metals, semiconductors, carbide, rubbers, ceramics and composites.



SPECIFICATIONS

Wavelength (nm)		532±1
Operating mode		Q-switched pulsed laser
Single pulse energy (μJ)		40~100uJ
Pulse duration (ns)		~5
Peak power (kW)		8~20
Rep. rate (kHz)	Uncontrollable	Undefined rep. rate among 5k-15kHz and unstable laser pulse emitting. Suitable for the applications only needing high peak power pulses.
Average power (mW)		Average power (mW) = Single pulse energy (μJ) * Rep. rate (kHz)
Ave power stability (over 4 hours)		<3%, <5%
Transverse mode		Near TEM ₀₀
Warm-up time (minutes)		<10
M ² factor		<1.5
Beam divergence, full angle (mrad)		<2.0
Beam diameter at the aperture (mm)		~4.0
Beam height from base plate (mm)		68.2
Operating temperature (°C)		10~35
Power supply (90-264VAC)		PSU-H-LED PSU-H-FDA PSU-N-OEM
Expected lifetime (hours)		10000
Warranty period		1 year



MPL-N-532	PSU-H-LED	PSU-H-FDA	PSU-N-OEM
<p>240(L)×99(W)×94(H) mm³, 2.6 kg</p>	<p>268(L)×145(W)×106(H) mm³, 2.6 kg</p>	<p>238 (L) ×146(W) ×102 (H) mm³, 2.3 kg</p>	<p>215 (L) ×129 (W) ×122 (H) mm³, 2.145 kg</p>