

**OEM-H-532/1-1000mW**
**LD PUMPED ALL-SOLID-STATE  
GREEN LASER**

All solid state 532 nm green laser is made features of ultra compact, long lifetime, low cost and easy operating. It's easy to be installed in customer's equipment.


**SPECIFICATIONS**

Wavelength (nm)	532±1	
Output power (mW)	>1, 5, 10, 100, ..., 500	500, 550, ..., 1000
Transverse mode	Near TEM <sub>00</sub>	
Operating mode	CW	
Power stability (rms, over 4 hours) at 25°C	<3%, <5%, <10%	
Warm-up time (minutes)	<10	
M <sup>2</sup> factor	<1.5	
Beam divergence, full angle (mrad)	1	
Beam diameter at the aperture (mm)	3	
Beam height from base plate (mm)	20	
Operating temperature (°C)	25+/−2	
Operating current of Diode (A)	0-2.5	0-5.5
Operating voltage of Diode (V)	~2.0	
Pins information	7/8: positive of diode; 3: negative of diode	5/6/7/8: positive of diode; 12/13/14/15: negative of diode
Power supply (optional)	PSU-III-OEM (5VDC)	PSU-OEM-F (two channels 6 & 12V)
Modulation option	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option	
Expected lifetime (hours)	5000	
Warranty time	The warranty is 3 months, excluding the LD failure.	

Note: The power supply needs to be with the over current protection function.



OEM-H-532	PSU-III-OEM (1-500mW)	Accessories	PSU-OEM-F (1-1000mW)	Accessories
 120(L)×32(W)×31(H) mm <sup>3</sup> , 0.245 kg	 100 (L) ×62(W) ×56 (H) mm <sup>3</sup> , 0.2kg	 120(L)×60(W)×37(H) mm <sup>3</sup> , 100-240VAC	 100(L)×76(W)×27(H) mm <sup>3</sup> , 0.10 kg	 160(L)×86.2(W)×34.5(H) mm <sup>3</sup> 100-240VAC Adapter