

OEM-XD-462/10000-15000mW


OEM BLUE DIODE LASER AT 462NM

OEM diode laser 462 nm blue laser is made features of ultra compact, long lifetime, low cost and easy operating. It's easy to be installed in customer's equipment.



SPECIFICATIONS

Model	OEM-XD-462	
Wavelength (nm)	462±3	
Output power (mW)	>10000, 11000..., 15000	
Operating mode	CW	
Power stability (rms, over 4 hours) at 25℃	<1%, <3%, <5%	
Warm-up time (minutes)	<5	
Beam divergence, half angle (mrad)	<1.8×0.4	
Beam diameter at the aperture (mm)	~5	
Polarization direction	Horizontal+ Vertical	
Beam height from base plate (mm)	35(OEM-XD-462)	89(XD-462-HS)
Operating temperature (℃)	25+/-3 (OEM-XD-462)	10-35 (XD-462-HS)
Power supply	PSU-N-LED / PSU-N-FDA/ PSU-HD-OEM-H	
Modulation option	TTL/Analog 1Hz-5KHz, 1Hz-10KHz, 1Hz-30KHz, and TTL on/off	
Expected lifetime (hours)	10000	
Warranty	1 year	



OEM-XD-462	XD-462-HS	PSU-N-LED	PSU-N-FDA	PSU-HD-OEM-H	Adapter
 200(L)×150(W)×60(H) mm³, 5kg	 226(L)×150(W)×115(H) mm³, 6.6 kg	 307(L)×150(W)×106(H) mm³, 2.6 kg	 307(L)×150(W)×106(H) mm³, 2.3 kg	 120(L)×88(W)×53(H) mm³, 0.20 kg	 211.2(L)×99(W)×50(H) mm³
